

R I S O G R A P H

CR1610



productive

compact

affordable



CR1610

>Finally, an alternative to costly photocopiers and restrictive laser printers: a fast, efficient, and cost-effective digital printing system that connects to your PC or Macintosh computer. The CR1610, engineered by RISO, the world leader in the development of digital duplicating systems, is the Risograph designed to meet the special requirements of smaller organizations. The CR1610 controls printing costs by using a unique patented inking and master-making system to bring the cost of printing down to as little as a fraction of a cent per page.

>With the CR1610's low operating costs and high reliability, you can double or even triple printing output without increasing printing expenditures. Plus, you can generate excitement and increase retention by adding spot color and printing on a variety of paper stocks, such as newsprint, construction paper, postcards, and envelopes. Take command of your printing and your budget with the CR1610, RISO's compact printing solution.



RISO, Inc.
300 Rosewood Drive
Danvers, MA 01923
Tel: 800.876.RISO (ext. 501)
www.riso.com

©Copyright 1999 RISO, Inc.
All products are trademarks of their respective companies. Specifications subject to change without notice.

Printed in USA

the *compact* printing solution

process	Risography (digital printing)
first copy time	25 seconds
printing speed	3 steps (60, 90, 130 pages/minute)
scanning resolution	300 x 300 dpi
original size and type	3.5" x 5.5" to 10.75" x 15.5" (90 x 140 mm to 274 x 395 mm), sheets
paper size and weight	3.5" x 5.5" to 10.75" x 15.5" (90 x 140 mm to 274 x 395 mm), 14# bond to 90# index (50 g/m ² to 107 g/m ²)
image area	CR1610 (110 VAC): 8.2" x 13.7" (210 x 349 mm) CR1630 (220 VAC): 9.8" x 14" (251 X 357 mm)
paper capacity	Feed Tray: 1000 sheets, 16# bond (64 g/m ²) Receive Tray: 1000 sheets, 16# bond (64 g/m ²)
ADF capacity	10 originals
preset reduction	CR1610 (110 VAC): 94%, 77%, 75%, 66% CR1630 (220 VAC): 94%, 87%, 82%, 71%
standard features	Print Speed Control, Photo Mode, Duo Mode, Auto Print Mode, Confidential Mode, Two- and Four-Up Printing, Programmable Print Grouping, Auto Scanning Contrast Adjustment, Interface Capabilities, Preventive Maintenance Indication
options	SC System Controllers, Color Print Cylinders, Job Separator, Key Card Counter, and Stand
electrical	110-220 VAC, 50/60 Hz <2-3A>
weight	141 lbs. (64 kg)
dimensions (w x d x h)	48.2" x 25" x 21.5" (1225 x 645 x 492 mm)



All Risographs are connectable to your stand-alone or networked PC and Macintosh®.



Item #1709